

PALLET FORKS

P45 | P60 | SEVERE DUTY



SPECIFICATIONS

- Pallet forks are available in lengths of 42, 48, and 60 inches check specifications below for vehicle compatibility).
- Skid-resistant steps on both sides of the pallet-fork frame ease vehicle entrance and exit.
- Single-piece backrest is available on P45 and P60 options. Severe-duty skid steer loader option includes a walk-through backrest with a bolt-on option.
- Severe-duty pallet forks offer increased capacity and durability over the previous fork-frame design.
- Brick-guard design provides strength and smooth surfaces, for protection against load damage.
- Design enables excellent visibility, and P45 and P60 standard frames include load-securing “D” ring.
- Quik-Tatch™ system allows easy attachment hook-up in seconds.
- These pallet forks are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They are compatible with most competitive models.

	HEAVY DUTY				SEVERE DUTY		
Machine	SSLs / CTLs			SSLs / CTLs	CWLs	SSLs / CTLs	
Model	P45			P60		PF45	PF60
Fork Tine Load Rating at 600-mm (24 in.) Load Center*	1814 kg (4,000 lb.)	2495 kg (5,500 lb.)	2812 kg (6,200 lb.)	2820 kg (6,200 lb.)	4490 kg (9,900 lb.)	4490 kg (9,900 lb.)	4490 kg (9,900 lb.)
Frame Width	1410 mm (55 in.)	1410 mm (55 in.)	1410 mm (55 in.)	1770 mm (70 in.)	1520 mm (60 in.)	1380 mm (54 in.)	1730 mm (68 in.)
Frame Height	990 mm (39 in.)	990 mm (39 in.)	990 mm (39 in.)	990 mm (39 in.)	535 mm (21.1 in.)	940 mm (37 in.)	940 mm (37 in.)
Overall Weight (frame and 2 tines)							
1065 mm (42 in.)	181 kg (397 lb.)	187 kg (412 lb.)	N/A	N/A	N/A	N/A	N/A
1220 mm (48 in.)	189 kg (416 lb.)	198 kg (435 lb.)	198 kg (435 lb.)	209 kg (459 lb.)	342 kg (754 lb.)	331 kg (729 lb.)	359 kg (790 lb.)
1520 mm (60 in.)	N/A	N/A	N/A	N/A	370 kg (816 lb.)	360 kg (793 lb.)	388 kg (854 lb.)
Overall Length (frame and 2 tines)							
1065 mm (42 in.)	1310 mm (52 in.)	1310 mm (52 in.)	N/A	N/A	N/A	N/A	N/A
1220 mm (48 in.)	1470 mm (58 in.)	1470 mm (58 in.)	1470 mm (58 in.)	1470 mm (58 in.)	1445 mm (56.9 in.)	1520 mm (60 in.)	1520 mm (60 in.)
1520 mm (60 in.)	N/A	N/A	N/A	N/A	1750 mm (68.9 in.)	1830 mm (72 in.)	1830 mm (72 in.)
Fork Thickness	36 mm (1.4 in.)	40 mm (1.6 in.)	45 mm (1.8 in.)	45 mm (1.8 in.)	50 mm (2 in.)	50 mm (2 in.)	50 mm (2 in.)
Fork Spacing	102 mm (4 in.)	102 mm (4 in.)	102 mm (4 in.)	102 mm (4 in.)	136 mm (5.35 in.)	127 mm (5 in.)	136 mm (5.35 in.)
Vehicle Compatibility	316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	184 G-Tier†, 204 G-Tier†, 244 P-Tier†, 304 G-Tier†, and 324 P-Tier† CWLs	330G and 332G SSLs; 331G and 333G CTLs	330G and 332G SSLs; 331G and 333G CTLs

*Pallet-fork capacity listed. Reference machine Operator's Manual for machine capacity.

†Requires skid-steer-style Quik-Tatch coupler for operation.

[Learn more about Pallet Forks](#)

[Back to Table of Contents](#)